

MOD. DSP26				DSP26	DSP26 add	
I	F	GB	D			
DATI TECNICI	DONNEES TECHNIQUES	SPECIFICATIONS	TECHNISCHE DATEN			
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN LxTxH	460x510x700	460x510x700	mm
CAPACITA' ORARIA cestelli/ora	DEBIT/H casiers/H	WASHING CAPACITY baskets/H	STUNDENLEISTUNG Körbe/Stunde	30	30	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	120	120	Sec.
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORB MAßE	40 x 40	40 x 40	cm
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFLÄCHENHÖHE	315	315	mm
LUCE DI CARICO	OUVERTURE DE CHARGEMENT	CLEARANCE	DURCHGANGSHÖHE	260	260	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	SPEISESPANNUNG	230 V~50Hz	230 V~50Hz	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	210	210	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	1000	1000	Hp
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	2400	2400	W
POTENZA NOMINALE	PUISSANCE NOMINALE	TOTAL RATING	GESAMTVERBRAUCH	2610	2610	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMAUFNAHME	12	12	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKFÜLLUNG	8	8	Lt
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERINHALT	3	3	Lt
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RINCAGE	RINSE AID DISPENSER	SPÜLMITTELDOSIERANLAGE	si-oui-yes-ja	si-oui-yes-ja	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLUß	12 ÷ 20	12 ÷ 20	°C
PORTATA ACQUA POMPA	PORTEE EAU MOTEUR	PUMP DELIVERY	UMWALZUNG WASCHPUMPE	160	160	l./min
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	CYCLE WATER CONSUMPTION	WASSERVERBRAUCH - ZYKLUS	2	2	l
CONSUMO ACQUA PER ORA	CONSOMMATION EAU HORAIRE	HOURLY WATER CONSUMPTION	WASSERVERBRAUCH - STUNDE	60	60	l
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	2 ÷ 4	2 ÷ 4	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOHLENE WASSERHÄRTE	5 ÷ 10	5 ÷ 10	°F
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RINÇAGE	RINSING WATER TEMPERATURE	SPÜLWASSERTEMPERATUR	80÷90	80÷90	°C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFANSCHLUß	3/4"	3/4"	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFANSCHLUß	32 mm ÷ 1"1/4	32 mm ÷ 1"1/4	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	39	39	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	43	43	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	VERPACKUNGABMESSUNGEN	500x630x900	500x630x900	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GERÄUSCH	<63	<63	dB(A)
ADDOLCITORE ACQUA INCORPORATO	ADOUCCISSEUR INCORPORE	INCORPORATED WATER-SOFTENER	WASSERENTKALKER	NON	YES	