

<b>MOD. A410-ek</b>				<b>A410-ek</b>	
I	F	GB	D		
<b>DATI TECNICI</b>	<b>DONNEES TECHNIQUES</b>	<b>SPECIFICATIONS</b>	<b>TECHNISCHE DATEN</b>		
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN LxTxH	<b>670X765X1475</b>	mm
CAPACITA' ORARIA piatti/ora	DEBIT/H assiettes/H	WASHING CAPACITY dishes/H	STUNDENLEISTUNG Teller/Stunde	<b>960-320</b>	Nr.
cestelli/ora	casiers/H	baskets/H	K rbe/Stunde	<b>60-30-20</b>	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	<b>60"-120"-180"</b>	Sec.
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORBAMA E	<b>50 x 50</b>	cm
NUM.PIATTI /CESTELLO	NUM.ASSIETTES PAR CASIER	DISHES PER BASKETS	TELLER PRO KORB	<b>12-16</b>	Nr.
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFL CHENH HE	<b>890</b>	mm
LUCE DI CARICO	OUVERTURE DE CHARGEMENT	PLATES CLEARANCE	DURCHGANGSH HE	<b>415</b>	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	VERSORGUNGSPANNUNG	<b>400 V3N~50Hz</b>	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	<b>1100</b>	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	<b>3000</b>	W
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	<b>9000</b>	W
POTENZA NOMINALE	PUISSANCE NOMINALE	TOTAL RATING	GESAMTVERBRAUCH	<b>10100</b>	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMAUFNAHME	<b>16</b>	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKF LLUNG	<b>34</b>	Lt
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERINHALT	<b>8</b>	Lt
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RIN AGE	RINSE AID DISPENSER	SP LMITTELDOSIERANLAGE	<b>si-oui-yes-ja</b>	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLU	<b>12 55</b>	C
PORTATA ACQUA POMPA	PORTEE EAU MOTEUR	PUMP DELIVERY	PUMPEWASSERMENGE	<b>480</b>	l./min
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	WATER CONSUMPTION PER CYCL	WASSERVERBRAUCH - ZYKLUS	<b>2.80</b>	l
CONSUMO ACQUA PER ORA	CONSOMMATION EAU HORAIRE	WATER CONSUMPTION PER HOUR	WASSERVERBRAUCH - STUNDE	<b>58-89-117</b>	l
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	<b>2 -- 4</b>	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOHLENE WASSERH RTE	<b>5 -- 10</b>	F
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RIN AGE	RINSING WATER TEMPERATURE	SP LWASERTEMPERATUR	<b>80 -- 90</b>	C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFROHRWEITE	<b>3/4"</b>	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFROHRWEITE	<b>32 mm -- 1"1/4</b>	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	<b>145</b>	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	<b>153</b>	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	VERPACKUNGABMESSUNGEN	<b>780x860x1430</b>	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GER USCH	<b>&lt;70</b>	dB(A)
<b>DOTAZIONI OPTIONAL</b>	<b>ACCESSOIRES</b>	<b>OPTIONALS</b>	<b>ZUBEH R</b>		
ADDOLCITORE	ADOUCCISEUR	WATER SOFTENER	ENTH RTER	<b>OPTION</b>	
POMPA DI SCARICO	POMPE DE VIDANGE	DRAIN PUMP	ABLAUFPUMPE	<b>30</b>	W
DOSATORE DI LAVAGGIO	DOSEUR DE PRODUIT DE LAVAGE	WASH AID DISPENSER	WASCHMITTELDOSIERANLAGE	<b>OPTION</b>	