

MOD. L21-ek/L21-ek-add				L21-ek	L21-ek-add	
I	F	GB	D			
DATI TECNICI	DONNEES TECHNIQUES	SPECIFICATIONS	TECHNISCHE DATEN			
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN l x t x h	620x765x1460	620x765x1460	mm
CAPACITA' ORARIA cestelli/ora	DEBIT/H casiers/H	WASHING CAPACITY baskets/H	STUNDENLEISTUNG Körbe/Stunde	30/20/15 60/30/20	30/20/15 60/30/20	Nr.
CAPACITA' ORARIA piatti/ora	DEBIT/H assiettes/H	WASHING CAPACITY dishes/H	STUNDENLEISTUNG Teller/Stunde	540/360/270(600) 1080/540/360(1200)	540/360/270(600) 1080/540/360(1200)	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	2÷3÷4 1÷2÷3	2÷3÷4 1÷2÷3	Min.
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORBMAßE	50 x 50	50 x 50	cm
NUM.PIATTI /CESTELLO	NUM.ASSIETTES POUR CASIER	PLATES PER BASKETS	N°.TELLER PRO KORB	12÷18 (20)	12÷18 (20)	Nr.
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFLÄCHENHÖHE	870	870	mm
LUCE DI CARICO	OUVERTURE DE CHARGEMENT	PLATES CLEARANCE	DURCHGANGSHÖHE	415	415	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	VERSORGUNGSPANNUNG	230/400/3f	230/400/3f	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	650	650	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	2000	2000	W
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	9000	9000	W
POTENZA TOTALE	PUISSANCE TOTALE	TOTAL RATING	GESAMTVERBRAUCH	9650	9650	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMSTÄRKE	16	16	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKKAPAZITÄT	34	34	l
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERKAPAZITÄT	5	5	l
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RINCAGE	RINSE AID DISPENSER	SPÜLDOSIERANLAGE	si-oui-yes-ja	si-oui-yes-ja	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLUß	45÷55	10÷12	°C
PORTATA ACQUA POMPA	PORTEE EAU MOTEUR	PUMP DELIVERY	WASSERMENGE	300	300	Lt/min.
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	CYCLE WATER CONSUMPTION	WASSERVERBRAUCH - ZYKLUS	2.60	2.60	Lt
CONSUMO ACQUA PER ORA	CONSOMMATION EAU ORAIRE	HOURLY WATER CONSUMPTION	WASSERVERBRAUCH - STUNDE	58 - 89 - 117	58 - 89 - 117	Lt
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	2 ÷ 4	2 ÷ 4	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOHLENE WASSERHÄRTE	5 ÷ 10	5 ÷ 10	°f
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RINCAGE	RINSING WATER TEMPERATURE	SPÜLWASSERTEMPERATUR	80 ÷ 90	80 ÷ 90	°C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFROHRWEITE	3/4"	3/4"	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFROHRWEITE	32 mm - 1" 1/4	32 mm - 1" 1/4	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	119	119	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	134	134	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	PACKUNGABMESSUNGEN	730x860x1610	730x860x1610	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GERÄUSCH	<63	<63	dB(A)
DOTAZIONI OPTIONAL	ACCESSOIRES	OPTIONAL	OPTIONAL			
POMPA DI SCARICO	POMPE DE VIDANGE	DRAIN PUMP	ABLAUFPUMPE	30	30	W
DOSATORE DI LAVAGGIO	DOSEUR DE PRODUIT DE LAVAGE	WASH AID DISPENSER	WASCHDOSIERANLAGE	OPTION	OPTION	