

<b>MOD. Minibar</b>				<b>Minibar</b>	
I	F	GB	D		
<b>DATI TECNICI</b>	<b>DONNEES TECHNIQUES</b>	<b>SPECIFICATIONS</b>	<b>TECHNISCHE DATEN</b>		
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN LxTxH	<b>482x510x690</b>	mm
CAPACITA' ORARIA cestelli/ora	DEBIT/H casiers/H	WASHING CAPACITY baskets/H	STUNDENLEISTUNG Körbe/Stunde	<b>30</b>	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	<b>120</b>	Sec.
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORB MAÛE	<b>40 x 40</b>	cm
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFLÄCHENHÖHE	<b>325</b>	mm
LUCE DI CARICO	OUVERTURE DE CHARGEMENT	CLEARANCE	DURCHGANGSHÖHE	<b>290</b>	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	SPEISESPANNUNG	<b>230 V~50Hz</b>	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	<b>210</b>	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	<b>1000</b>	W
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	<b>2400</b>	W
POTENZA NOMINALE	PUISSANCE NOMINALE	TOTAL RATING	GESAMTVERBRAUCH	<b>2600</b>	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMAUFNAHME	<b>12</b>	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKFÜLLUNG	<b>8</b>	Lt
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERINHALT	<b>3</b>	Lt
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RINCAGE	RINSE AID DISPENSER	SPÜLMITTELDOSIERANLAGE	<b>si-oui-yes-ja</b>	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLUß	<b>10 ÷ 12</b>	°C
PORTATA ACQUA POMPA	PORTEE EAU MOTEUR	PUMP DELIVERY	UMWALZUNG WASCHPUMPE	<b>160</b>	l./min
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	CYCLE WATER CONSUMPTION	WASSERVERBRAUCH - ZYKLUS	<b>2</b>	l
CONSUMO ACQUA PER ORA	CONSOMMATION EAU HORAIRE	HOOR WATER CONSUMPTION	WASSERVERBRAUCH - STUNDE	<b>60</b>	l
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	<b>2 ÷ 4</b>	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOHLENE WASSERHÄRTE	<b>5 ÷ 10</b>	°F
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RINÇAGE	RINSING WATER TEMPERATURE	SPÜLWASSERTEMPERATUR	<b>80÷90</b>	°C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFANSCHLUß	<b>3/4"</b>	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFANSCHLUß	<b>32 mm ÷ 1"1/4</b>	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	<b>43</b>	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	<b>48</b>	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	VERPACKUNGABMESSUNGEN	<b>600x500x910</b>	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GERÄUSCH	<b>&lt;60</b>	dB(A)
<b>DOTAZIONI OPTIONAL</b>	<b>ACCESSOIRES</b>	<b>OPTIONAL</b>	<b>OPTIONAL</b>		
DOSATORE DI LAVAGGIO	DOSEUR DE PRODUIT DE LAVAGE	WASH AID DISPENSER	WASCHMITTELDOSIERANLAGE	<b>OPTION</b>	